

PATENT

ATTORNEY DOCKET NO.: TCZ-39

UNITED STATES PATENT APPLICATION

FOR

DECORATIVE TEXTURIZED FABRIC

BY

MARTIN WILDEMAN

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

TITLE OF THE INVENTION

DECORATIVE TEXTURIZED FABRIC

5

RELATED APPLICATIONS

The present application is based on a Provisional Application filed on August 23, 2000 having U.S. Serial No. 60/227,236.

FIELD OF THE INVENTION

10 The present invention generally relates to decorative warp knitted fabrics suitable for use in home furnishings and in other related applications.

BACKGROUND OF THE INVENTION

15 Home furnishing fabrics, such as upholstery fabrics, are designed to not only be durable but have aesthetic appeal. In some applications, the fabrics are highly engineered in order to provide the fabric with a unique look or design. In general, such fabrics can have two types of designs. The first type is a design that is created with color, such as by using different colored yarns to weave the fabric.

20 The second type of fabric design is created by changing the texture of the fabric in a manner that creates visual pattern. For instance, in one embodiment, the texture of the fabric can be changed by changing the weave. For example, a jacquard weaving system is a system of weaving that utilizes a highly versatile pattern mechanism to

permit the production of large, intricate designs. Jacquard weaving systems are very complicated and provide the ability to control the action of each warp thread during the passage of a single pick. Jacquard weaving is used to create tapestry, brocade, damask, and the like.

5 Unfortunately, fabrics produced on a jacquard weaving system and other similar fabrics containing textured patterns can be relatively expensive to produce. As such, a need currently exists for an inexpensive alternative to producing fabrics having a textured pattern. A need also exists for a textured pattern having a unique appearance in
10 comparison to conventional fabrics.

SUMMARY OF THE INVENTION

 The present invention is generally directed to a decorative fabric product and to a process for making the product. Fabric products made in accordance with the present invention have a distinctive and aesthetic
15 textured pattern. The fabrics are well suited for uses in many diverse applications, such as being used in the home furnishings field.

 In one embodiment, the process for producing the fabric product includes the steps of providing a fabric substrate having a face side and a back side. The fabric substrate contains a first yarn that is nappable
20 from the face side of the fabric substrate. A size composition is applied to the face side of the fabric substrate according to a particular pattern such that the face side includes size treated areas and untreated areas.

The size composition can include, for instance, a copolyester, a starch or a polyvinyl alcohol.

After the size composition is applied to the face side of the fabric, the face side is then napped using a napping device. During napping,

5 the first yarn is napped in the untreated areas creating a fabric product having a textured pattern. If desired, once the fabric is napped, the size composition can be removed from the fabric substrate. For example, the fabric can be scoured in order to remove the size composition.

Subsequently, the fabric can be dyed.

10 In one embodiment, the fabric substrate is a warp knitted fabric. The warp knitted fabric can contain at least two yarns. The first yarn can have a denier that is greater than the second yarn. The first yarn can predominantly form the face side of the fabric. For example, the first yarn can be a multifilament polyester yarn having a denier of from about
15 50 to about 200. The first yarn can be knitted into the fabric substrate in a manner that forms from about 14 to about 40 knitted rows per inch.

The second yarn, on the other hand, can be a monofilament polyester yarn. The second yarn can be knitted into the fabric substrate according to a chain stitch notation for providing integrity substrate.

20 The size composition can be applied to the face side of the fabric substrate in various manners. For instance, the size composition can be sprayed onto the fabric or printed onto the fabric. Printing the size

composition onto the fabric allows the size composition to be applied to the fabric in particular discrete areas.

Besides the above process, the present invention is also directed to a fabric product having a textured surface. In one embodiment, the fabric product includes a warp knitted fabric containing at least a first yarn and a second yarn. The warp knitted fabric has a face surface and a back surface. The fabric is formed in a manner such that the face surface is predominantly comprised of the first yarn. For instance, the first yarn can be knitted into the fabric so as to form knitted rows visible from the face side. For example, the first yarn can form from about 14 to about 40 knitted rows per inch.

In accordance with the present invention, the warp knitted fabric is subjected to a napping process that selectively naps the first yarn from the face surface to form a textured pattern. In order to form the textured pattern, a size solution can be applied to the fabric prior to the napping process. The size solution prevents the first yarn from being napped from the surface thus allowing for a textured pattern to be formed.

Other features and aspects of the present invention are discussed in more detail below.

BRIEF DESCRIPTION OF THE DRAWINGS

A full and enabling disclosure of the present invention, including the best mode thereof, directed to one of ordinary skill in the art, is set

forth more particularly in the remainder of the specification, which makes reference to the appended figures in which:

Figure 1 is a magnified plan view of a fabric made in accordance with the present invention;

5 Figure 2 is a further magnified plan view of the fabric shown in Figure 1.

Repeat use of reference characters in the present specification and drawings is intended to represent same or analogous features of the invention.

10 **DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS**

It is to be understood by one of ordinary skill in the art that the present discussion is a description of exemplary embodiments only, and is not intended as limiting the broader aspects of the present invention, which broader aspects are embodied in the exemplary constructions.

15 The present invention is generally directed to a decorative fabric having an aesthetic appearance. In particular, the fabric of the present invention includes a texturized pattern produced through a napping process. The fabric has many useful and diverse applications. For instance, the fabric is well suited to being used in the home furnishings
20 field such as an upholstery fabric or as a fabric used to make curtains and the like. Of particular benefit, the fabric of the present invention is

relatively inexpensive to produce in comparison to many conventionally made fabrics.

In general, the fabric of the present invention is a knitted fabric, such as a warp knitted fabric. Warp knitting refers to a type of knitting in which the yarns generally run lengthwise in the fabric. The yarns are prepared as warps on beams with one or more yarns for each needle. Examples of warp knitted fabrics include tricot, milanese, and raschel knitted fabrics. Warp knitted fabrics made in accordance with the present invention typically contain at least two yarns.

Although generally the present invention is directed to the use of a warp knitted fabric, it should be understood that a suitable woven fabric can also be used to construct the fabric product of the present invention. For a woven fabric to be suitable in the present invention, the woven fabric should be capable of withstanding a napping process and should include a yarn that is nappable from at least one side of the fabric. Since the use of warp knitted fabrics is preferred, however, the remainder of the following description will refer primarily to such fabrics.

In order to create a texturized pattern into the warp knitted fabric according to the present invention, a size composition is applied to the fabric according to a predetermined pattern. Once the size is applied, the fabric is then subjected to a napping process. Napping is a process that raises the surface fibers of the fabric by passing rapidly revolving

cylinders covered with metal points or teasel burrs over the surface of the fabric. As used herein, napping is also intended to include brushing in which rotating brushes raise a nap on the fabric.

It has been discovered by the present inventor that when a fabric
5 is napped according to the present invention, a nap is formed on the surface of the fabric where the size composition has not been applied. This process produces a textured pattern having an appealing look and feel.

One embodiment of a process made in accordance with the
10 present invention will now be discussed in detail. As stated above, the fabric of the present invention is a warp knitted fabric constructed from at least two yarns. In other words, the warp knitted fabric can be referred to as a two bar fabric meaning that the fabric is made on a two bar knitting machine in which two yarn sheets are fed to two independent guide bars.
15 It should be understood, however, that three or more bars may also be used to produce the fabric.

The basis weight of the warp knitted fabric can vary depending upon the particular application. For most applications, however, the basis weight of the fabric will be from about 2osy to about 6osy, such as
20 from about 2.5osy to about 3.5osy.

The first yarn used to construct the fabric generally creates the face of the fabric. As used herein, the face of the fabric, the face side of

the fabric, or the face surface of the fabric refers to the side of the fabric that includes a textured pattern made according to the present invention and is intended to be the decorative side of the fabric. The first yarn is knitted into the fabric in multiple rows. For instance, the first yarn can be knitted into the fabric using a bar having from about 14 needles per inch to about 40 needles per inch and, in one embodiment, having 32 needles per inch which forms a corresponding number of rows.

The course density of the first yarn can vary widely from about 20 courses per inch to about 60 courses per inch, and particularly from about 40 courses per inch to about 50 courses per inch.

The first yarn can be made from various materials, such as polyester. In one embodiment, the yarn can be a multifilament yarn having a denier of from about 50 to about 200. For example, in one embodiment, a 70 denier bright trilobal flat yarn can be used made from about 36 filaments.

The stitch that is used for the first yarn can also vary. In one embodiment, a 1, 0/3, 4 pattern notation can be used.

The second yarn used to form the warp knitted fabric generally forms the back of the fabric opposite the face side. In one embodiment, the second yarn can be chain stitched during formation of the fabric. For example, the chain stitch can have a 1, 0/1, 0 closed chain stitch notation.

Similar to the first yarn, various different yarns can be used as the second yarn to form the fabric without limitation. In one embodiment, the second yarn can be a monofilament polyester yarn. The yarn can have a denier of from about 10 to about 50, such as a denier of about 20.

5 Once the fabric is formed, a size composition is then applied to the fabric according to a predetermined pattern. For instance, the size composition can be printed onto the fabric. For example, in one embodiment, a Stork PD-3 rotary screen printer can be used. The size composition is applied to the fabric where it is desired for the fabric not to
10 be napped.

 Various designs can be applied to the fabric as desired. For instance, the size composition can be printed onto the fabric to form flowers, animals, designs, logos, and the like. Alternatively, the size composition can be applied to the fabric according to a geometric pattern
15 or according to an abstract pattern that has the appearance of being random.

 Any suitable size composition can be used in accordance with the present invention. More particularly, a size composition should be used that is capable of being printed and that will render a fabric resistant to
20 napping. Examples of size compositions include copolyester compositions, starch compositions or polyvinyl alcohol compositions.

In one embodiment, Eastman WD copolyester size can be used. In order to facilitate printing of the size onto the fabric, a thickener or other agents can be added to the size.

In one particular embodiment, the size composition can include
5 the following:

<u>Component</u>	<u>Weight %</u>
Water	44.50
Eastman WD Size	50.00
Apex Defoamer PRT	0.50
10 Glotex Concentrate T1	5.00

After the size composition is applied to the fabric, the composition should be dried. For example, the fabric can be applied to a tenter frame and fed through the printing device. After printing, the fabric can then be processed through an oven at a temperature of about 390 degrees F for
15 a time sufficient for the size composition to dry.

After the size composition is applied to the fabric and dried, the fabric is then subjected to a napping process in accordance with the present invention. The napping device that contacts the face of the fabric can include burrs, such as teasel burrs, brushes, or a combination
20 of both. For instance, a UNIPRO double action napper can be used which is manufactured by Gessner. During napping, the napping device raises the surface fibers of the fabric where the fabric has not been

sized. The size composition, however, renders the fabric resistant to napping and allows the fabric to maintain a smooth surface.

Where the size composition has not been applied to the fabric, however, the napping process creates a downy surface or nap that
5 provides contrast to the areas where the size has been applied.

After napping, the size is removed from the fabric and the fabric can be dyed if desired. For instance, in one embodiment, the fabric can be loaded onto a beam dye machine. Once wound onto a beam, hot water is pumped through the beam which removes the size. In one
10 embodiment, a detergent, such as a non-ionic detergent can be added to the water pumped through the beam. The detergent can be added in an amount up to about 1 percent by weight, such as from about 0.2 percent to about 0.5 percent. The temperature of the water fed through the beam will vary depending upon the size composition. In one
15 embodiment, the water is at a temperature of 190 degrees F.

Hot water is circulated through the beam until the size is completely removed. Once the size is removed, the hot water can be replaced with a dye and the fabric can be dyed.

After being scoured to remove the size and dyed, the fabric can
20 be placed on a tenter frame and heat set. For example, in one embodiment, the fabric can be fed through an oven set at a temperature of about 380 degrees F.

Referring to Figures 1 and 2, one embodiment of a fabric generally 10 made in accordance with the present invention is illustrated. As shown, fabric 10 is a warp knitted fabric containing rows of stitches 12 made from the first yarn.

5 In accordance with the present invention, the fabric further includes texturized or nap areas 14 and smooth areas 16. The smooth areas 16 are located where the size composition was applied. As shown, a striking contrast in texture is formed between the two areas. In this manner, many distinctive designs can be formed into the fabric for
10 increasing the aesthetic appeal of the fabric.

These and other modifications and variations to the present invention may be practiced by those of ordinary skill in the art, without departing from the spirit and scope of the present invention. In addition, it should be understood that aspects of the various embodiments may be
15 interchanged both in whole or in part. Furthermore, those of ordinary skill in the art will appreciate that the foregoing description is by way of example only, and is not intended to limit the invention.